



# COBRA AMERICA



## TECHNICAL DATA SHEET- CLEATED MINI BYTE

Delta 150 PIW 2 Ply 1/16 X BARE, RMAII

### DIMENSIONS AND CONSTRUCTION

|                                      |                 |
|--------------------------------------|-----------------|
| Belt fabric                          | Plied/Polyester |
| Number of plies                      | 2 ply           |
| Overall belt gauge                   | 3/16 Inches     |
| Top cover thickness                  | 1/16 Inch       |
| Bottom cover thickness               | BARE            |
| Width Tolerance                      | ±1 %            |
| Approx. Weight - Lbs. Per Inch Width | .121 Pounds     |

### MECHANICAL PROPERTIES

|                                          |             |
|------------------------------------------|-------------|
| Tensile Strength at Break                | 1500 Pounds |
| Longitudinal elongation at break         | 10 %        |
| Elongation under maximum working tension | 1.5 %       |
| Adhesion between cover and carcass       | 45 PIW      |
| Adhesion between plies and plies         | 45 PIW      |

### COVER MECHANICAL PROPERTIES

|                     |                     |
|---------------------|---------------------|
| Tensile strength    | 12 MPa              |
| Elongation at break | 400 %               |
| Abrasion index      | 220 mm <sup>3</sup> |
| Temperature index   | -13° F - 176° F     |

